

## Technical Data – Rotary CFA / DTHH Drilling Rigs



We operate a tracked, self-propelled Sedi Drill 90 rotary investigation rig, which incorporates a Lutz-Data-Logger in order to record the rate of drilling and thrust and torque pressures. .

This 900mm wide rubber tracked (6kpa ground pressure) rig is particularly useful on difficult or narrow access sites. It has low noise levels and low visual impact.

Hollow Stem and Solid Stem Flight augers are used for rapid drilling to 20m or more. The augers are available in a range of diameters; Solid Stem 115mm and 200mm, Hollow Stem 165mm with 80mm keyway.

Hollow stem augers can be used as a casing for the installation of prefabricated and conventional monitoring wells up to 80mm outer diameter (including filterpack)

In order to provide for a wide variety of ground conditions and sampling requirements, the rig is also equipped for rotary drilling (Down-The-Hole-Hammer).

<b>Sedi Drill 90</b>	
Pullback (kg)	1500
Fuel	Diesel
Gross weight excluding tools (kg)	1660
Travelling dimensions – length (mm)	2750
width (mm)	920
height (mm)	1250
Operating dimensions – length(mm)	2600
width (mm)	1400
height (mm)	3100

*Note: All dimensions are approximate and should be checked prior to mobilisation to site*

Southern Testing Head Office  
East Grinstead  
Tel: 01342 333100  
enquiries@southernesting.co.uk

ST Consult Midlands  
Northampton  
Tel: 01604 500020  
creaton@stconsult.co.uk

ST Consult North West  
Warrington  
Tel: 01925 661 700  
warrington@stconsult.co.uk

ST Consult South West  
Swindon  
Tel: 01793 441 522  
swindon@stconsult.co.uk



FS 29280

EMS 506775

OHS 506776

